

Blow-moulding

Polyethylene / Polypropylene





Repsol. A global multi-energy company

Over 8 decades of experience in the world of energy

One of the largest energy companies worldwide and one of the biggest private oil & gas companies.

Repsol is committed to our customers' global strategy putting our entire organization at their disposal to achieve a common goal: to create long-term relationships which enable us to rise to the common challenges our business presents.



Repsol has a diverse workforce of over 25,000 employees, marketing products in over 90 countries and reaching 10 million customers. Repsol's highly integrated Chemical Division focuses its strategy on the continuous generation of value through differentiated products and services.

Repsol Campus, Corporate Headquarters in Madrid

LEED[®] Platinum certificate, awarded by the prestigious U.S. Green Building Council (USGBC), for new buildings construction



Over 90 countries where we market our products



Added value

Repsol's Chemicals Division, with a high degree of integration, focuses its strategy in the constant generation of value through differentiated products and services.

Over 1,500 references

Base petrochemicals: ethylene, propylene, butadiene and benzene.

Intermediate products: styrene, propylene oxide, polyether polyols, and propylene glycols.

copolymers.



Including qualified personnel specialised on Product Stewardship.

business excellence to meet future horizons.

- Repsol manufactures a wide variety of products, ranging from base petrochemicals to derivatives
- **Polyolefins:** polypropylene (PP) and PP compounds, both high and low-density polyethylene (HDPE and LDPE), metallocene linear low density polyethylene (mLLDPE), ethylene vinyl acetate (EVA) and ethylene butyl acrylate (EBA)

- Repsol's commitment to R&D is an evidence of the company's aim to attain

Working for a more

At Repsol, we believe in the circular economy and we run specific projects that minimise the environmental impact of our materials. To this end, we are committed to making our industrial processes increasingly efficient and reducing the carbon footprint of our polymers.


technical performance.

sustainable future

We are a driving force in the circular economy for plastics and we are a member of the "Circular Plastics Alliance", an initiative launched by the European Commission for ten million tonnes of recycled plastic to find their way into new products in the European market by 2025, in line with the strategy for the circular plastics economy published by the Commission in 2018.

We have a specialised department dedicated to the circular economy and the recycling of materials after consumption to drive the development of new materials offering innovative technical polyolefin solutions. We use recycled plastics in critical applications, creating new markets for plastic waste and incentivising circularity by giving it a new use. As a result, we provide a wide range of products for rigid blow-moulded packaging offering excellent

Blow-moulding





We have been developing our integrated chemical business for over 40 years and this experience allows us to control all of the key factors in the value chain: research, development, manufacture, marketing and distribution. With three integrated production facilities in the Iberian Peninsula, we have experience in high-cleanliness product launches with strict handling procedures in place and we provide a regular supply of materials to the food packaging industry.

Tech 4 **Over 30 years of experience** in technical services and development


Our Technology Lab Centre is the hub of our innovation and development. This is where our products come to life and are meticulously perfected in our quest for innovative solutions to meet our customers' needs. Our mission is to develop cutting-edge products and offer high-quality solutions to improve your business.



Blow-moulding

Over 30 blow-moulding grades

Thanks to our versatility, we are able to produce one of the widest ranges of polyolefins on the market for industrial sectors such as:



If foodstuffs were packaged with other materials, energy consumption would double and greenhouse gas emissions would almost triple. And all of this would also suppose a 360% increase in packaging weight!











Dairy and food products

Thanks to their greater density, our grades offer high rigidity from thinner material. Safety is our priority, and this has positioned us in the most demanding markets in terms of food safety.



Grade	Density	M	FI	Tensile strentgh at break	ESCR	Flexural modulus	Container capacity	Main application
	kg/m³	ISO1133 (1 9 2.16 kg	30°C) g/10' 21.6 kg	ISO527-2 MPa	ASTM 1693 ⁽¹⁾ h (F50)	ISO178 MPa	Litres	
6006L	963	0.6	40	18	< 10	1450	< 5	Packaging for dairy products and other foods
6006B ⁽²⁾	972	0.6	40	18	< 10	1450	< 5	White bottles for dairy products and other foods
5703L	962	0.3	30	30	15	1550	< 5	Packaging for dairy products and other foods

(1) 10% Igepal. 50°C.

(2) Contains 1.25% TiO₂.



We are food safety leaders. All of our facilities are FSSC 22000 certified in recognition of our food safety risk management processes throughout the supply chain





Dairy and food products

Polypropylene

Grade	MFI	Flexural modulus	Tensile strengh at yield	Izod impact strength notched	Container capacity	Main application
	ISO1133 (230°C) g/10' 2.16 kg	ISO178 MPa	ISO527-2 MPa	ISO180/1A kJ/m²	Litres	
PR230C1E	1.6	800	27	22	< 10	Transparent containers
RC530S2E	1.6	800	27	22	< 10	Very high gloss, transparency and clarity contai
PP020G3E	0.91	1200	34	-	< 10	Thin walled containers
PP030G1E	1.7	1250	34	-	< 10	Thin walled containers

We have a Product Stewardship department which ensures strict compliance with all of the legislation governing contact with foodstuffs





Household goods and cosmetics

Our commitment to the environment has driven us to new developments. The **new Repsol Reciclex® range** offers compounds using up to 50% of recycled material for the extrusion blow moulding of packaging.

HDPE

Grade	Density	٢	1FI	Tensile strentgh at break	ESCR	Flexural modulus	Container capacity	Main application
	kg/m³	ISO1133 (1 2.16 kg	90°C) g/10' 21.6 kg	ISO527-2 MPa	ASTM 1693 ⁽¹⁾ h (F50)	ISO178 MPa	Litres	
5203	950	0.23	20	27	60	1100	< 10	Packaging for household products, cosmetics and
5502E	955	0.23	22	28	35	1200	< 20	Packaging for household products, cosmetics and
5503	955	0.25	25	28	100	1200	< 20	Packaging for agressive households chemical pro
5803 ^[2]	958	0.25	26	30	200	1400	< 20	Packaging for agressive households chemical proc

(1) 10% Igepal. 50°C.

(2) Bimodal.

LDPE

Grade	Density	MFI	Production process	Container capacity	Main application
	kg/m³	ISO1133 (190°C)g/10' 2.16 kg		Litres	
PE003	920	2	Autoclave	< 2	Soft containers for detergents and cosmetics
2308F	923	0.8	Tubular	< 2	Soft containers for detergents and cosmetics
PE033	921	0.3	Autoclave	< 2	Soft containers for detergents and cosmetics

The information contained herein is based on REPSOL QUIMICA's current knowledge and experience and is presented in good faith for guidance only. Although REPSOL QUIMICA declares to have been most diligent when including the information contained herein, taking into account that several and different factors may affect the processing, application or use of the products, the convertor shall be responsible in every case for the conditions under which the products are transformed as well as for the final use given to them. REPSOL QUIMICA warns that this information may undergo variations or improvements; therefore REPSOL QUIMICA is not obliged to reflect these in this document or to communicate them to whomever may have access to it. Moreover, these readers should be aware that some or all of the products might be protected by intellectual property rights. © REPSOL QUIMICA, S.A. 2019. All rights reserved.





roducts. High rigidity



Household goods and cosmetics

Polypropylene

Grade	MFI	Flexural modulus	Tensile strengh at yield	Izod impact strength notched	Container capacity	Main application	Othe
	ISO1133 (230°C) g/10' 2.16 kg	ISO178 MPa	ISO527-2 MPa	ISO180/1A kJ/m²	Litres		
PR230C1E	1.6	800	27	22	< 10	Transparent containers	
RC530S2E	1.6	800	27	22	< 10	Very high gloss, transparency and clarity containers	
PP020G3E	0.91	1200	34	-	< 10	Thin walled containers	High tenacity strapping, sheet ex
PP030G1E	1.7	1250	34	-	< 10	Thin walled containers	High tenacity strapping, sheet ex
PB110H2E	0.3	1300	45	-	< 10	Containers < 10l	High shine sheet extrusion, pipes
PB130G1F	1.3	1100	27	-	< 10	Containers < 10l	Excellent gloss



Safety is a priority: we are OHSAS 18001 (Occupational Health and Safety Assessment Series) certified in recognition of our strict safety management





Industrial packaging

We are leading suppliers to the chemical, lubricant, fuel and food industries.

HDPE

Grade	Density		MFI	Tensile strentgh at break	ESCR	Flexural modulus	Container capacity	Main application
	kg/m³	ISO1133 2.16 kg	(190°C) g/10' 21.6 kg	ISO527-2 MPa	ASTM 1693 h (F50)	ISO178 MPa	Litres	
5803 ⁽⁾	¹⁾ 958	0.25	26	30	200	1400	< 20	Packaging for detergents and chemical products
450600	y ⁽²⁾ 945	< 0.1	6	35	> 1000	1000	700 - 4000	IBC's and domestic fuel containers
49070U\	/ ^[2] 949	< 0.1	9	30	> 400	1000	700 - 4000	IBC's and domestic fuel containers
55050	955	< 0.1	5.5	38	> 200	1350	< 200	Jerrycan and open top drums for chemical

(1) Bimodal.

(2) UV protected.



Our high molecular weight grades for packaging for the transport of hazardous and aggressive materials are lighter, while their rigidity and high resistance to cracking mean they use less material





Automotive


We have grades suitable for high value-added products such as fuel tanks, aeration tubing and other motor vehicle parts, through our continuous development processes.

HDPE

Grade	Density MFI		FI	Tensile strentgh at break	ESCR	Flexural modulus	Main application
	kg/m³	ISO1133 (19 2.16 kg	0°C) g/10' 21.6 kg	ISO527-2 MPa	ASTM 1693 ⁽¹⁾ h (F50)	ISO178 Мра	
5203	950	0.23	20	27	60	1100	Blow molding automotive products
5502E	955	0.23	22	28	35	1200	Blow molding automotive products
5503	955	0.25	25	28	100	1200	Blow molding automotive products
45060	945	< 0.1	6	35	> 1000	1000	Plastic fuel tanks

(1) 10% Igepal. 50°C.

All of the activities of the Chemical Division at Repsol are ISO 9001 quality certified. Our industrial facilities meet the ISO 14001, ISO 50001 and OHSAS 18001 (Occupational Health and Safety Assessment Series) standards







Excellence is intrinsic to Repsol's values. It infuses our daily work and helps guide our decisions and actions, contributing to achieve the commitment made to our customers, stakeholders, employees, suppliers / partners and society to build a better future.

Safety is our priority

Petrochemical complexes, packaging facilities and logistics centres all have OHSAS 18001.2007 (Occupational Health and Safety Assessment Series) certification for their rigorous safety measures. Technical Data Sheets and MSDS are available on: www.repsol.com

> Petrochemical plants, packaging production plants and logistics

All industrial complex



All Repsol's polyolefins production centers are FSSC 22000 certified

OHSAS 18001.2007

FSSC 22000

Repsol supplies grades with excellent properties, specially designed for applications with stringent quality specifications



Quality

All petrochemical plants are compliant with the current ISO 9001:2015 standards, for the quality of processes from manufacture to distribution, transport management and end product warehousing.

All petrochemical plants

Environment

We set up and deploy ambitious energy efficiency programmes to reduce energy consumption and GHG emissions as one of the key elements of our strategy. These programmes pursue long term targets which have been made public in order to facilitate their progress by the stakeholders. In this sense, Repsol Química has attained a final reduction of 0.56 million tonnes of GHG emissions at the end of the 2006-2013 period. Repsol is currently working on a new target covering the period 2014-2020, that involves an additional reduction of 0.42 million tonnes of CO₂. The Chemical area of our complexes in Tarragona (2015), Puertollano (2013) and Sines (2016), has implemented an Energy Management system according to the requirements indicated in the International Standard ISO 50001. This system is dedicated to developing and implementing our organization's energy policy, as well as manage the energy aspects of our activities, products or services. The objective is to increase and improve our energy efficiency, based on systems' implementation aimed at continuous energy performances improvement and thus contribute to a more efficient and sustainable use of energy.

All petrochemical complexes, have ISO 14001 certification for their environmental management and the reduction of the impact of their facilities; and ISO 14064 for the annual verification of greenhouse gas (GHG) emissions. Repsol reinforced its commitment with sustainability by signing the "Paris Pledge for Action" document. An historical agreement in which both developed countries and less developed countries and companies engaged to contribute towards a low CO, emission economy.

Puertollano, Tarragona and Sines

ISO 9001:2015

ISO 50001 / ISO 14001 / ISO 14064

Chemicals Customer Care

SPAIN

Tel.: 900 10 32 39 Tel.: +34 91 753 18 01

PORTUGAL

Tel.: 800 60 501 111 Tel.: +34 91 753 18 05

FRANCE

Tel.: 800 60 503 333

ITALY

Tel.: 800 60 509 999 Tel.: +34 91 753 18 04

GERMANY

Tel.: 800 60 504 444 Tel.: +34 91 753 18 00

UNITED KINGDOM

Tel.: 800 60 502 222

www.repsol.com

Intrapreneurship

Results Orientation Inspiring Leadership Collaboration Accountability



Corporate Headquarters

Méndez Álvaro, 44 28045 Madrid. Spain Tel.: +34 91 753 81 00 www.repsol.com

Technical Service & Development Repsol Technology Lab

28931 Móstoles, Madrid. Spain Tel.: +34 91 753 86 00 atd_poliolefinas@repsol.com

Results Orientation

Intrapreneurship

Inspiring Leadership Collaboration Accountability

